

KOMPRESOL L-DAA

APPLICATION

KOMPRESOL L-DAA compressor oils for lubrication of medium duty piston air compressors as well as rotary and vane compressors.

KOMPRESOL L-DAA compressor oils may be mixed with and replaced by compressor oils from other manufacturers - within the same grade of viscosity and quality.

ADVANTAGES

- Good protection from mechanical wear
- High resistance to oxidation and ageing
- Ensure accurate corrosion protection



STANDARDS, SPECIFICATIONS

ISO 6743/3A: L-DAA
DIN 51506 VBL

Parameters	KOMPRESOL L-DAA	
	L-DAA 68	L-DAA 100
Appearance at 20°C	clear, homogeneous oil	
Kinematic viscosity at. 40°C, [mm ² /s]	66	98
Viscosity index	95	
Pour point, [°C]	-14	-11
Flash point, [°C]	210	220
Notice: The above parameter values are typical. The actual values are to be found in the laboratory report attached to each batch of the product.		

ADDITIONAL INFORMATION

Chemnaft oils need to be stored in steel or polyethylene containers protecting the product from damp and mechanical impurities. Given the available knowledge, the product does not have an adverse impact on humans, if used properly. Safety information is to be found in the current material safety data sheet.



Chemnaft Sp. z o.o. S.K.A.
Brzeście Nowe 11B/2, 09-130 Baboszewo
NIP 9581664337
www.chemnaft.com