

# GUIDE OIL RC

## APPLICATION

RC guide oils for lubricating all types of sliding guides (horizontal and vertical) operating in elevated temperatures under high loads. They guarantee proper operation of guides with special emphasis on adequate friction and elimination of the stick-slip effect.

## ADVANTAGES

- Ensures adequate adhesion to lubricated elements
- Prevents stick-slip effect
- Good protection from mechanical wear
- Ensure accurate corrosion protection



## STANDARDS, SPECIFICATIONS

ISO 3448: ISO VG 68, 220

DIN 51502 CGLP

ISO 6743-13:2002/G

Parameters	GUIDE OILS RC	
	RC 68	RC 220
Appearance at 20°C	Clear oil, without suspended solids or deposits	
Kinematic viscosity at. 40°C, [mm <sup>2</sup> /s]	69	224
Viscosity index	96	
Pour point, [°C]	-15	-10
Flash point, [°C]	225	235
<b>Notice:</b> The above parameter values are typical. The actual values are to be found in the laboratory report attached to each batch of the product.		

## ADDITIONAL INFORMATION

Chemnaft oils need to be stored in steel or polyethylene containers protecting the product from damp and mechanical impurities. Given the available knowledge, the product does not have an adverse impact on humans, if used properly. Safety information is to be found in the current material safety data sheet.



**Chemnaft Sp. z o.o. S.K.A.**  
**Brzeście Nowe 11B/2, 09-130 Baboszewo**  
**NIP 9581664337**  
[www.chemnaft.com](http://www.chemnaft.com)