

TRAKOL CD 15W/40

APPLICATION

Mineral motor oil for various types of light- and heavy duty diesels, turbo- or super-charged. Ensures excellent lubrication of engines in truck tractors, trucks and off-road vehicles. Also suitable for worn-out engines. Can be used throughout the year – guarantees easy startup of the engine in winter as well as proper lubrication parameters in a wide temperature range.

ADVANTAGES

- Good washing and dispersing properties
- Ensures lubrication even under heavy thermal and mechanical loads
- Prevents piston rings from seizing



STANDARDS, SPECIFICATIONS

API: CD

SAE: 15W/40

| Parameters | TRAKOL CD 15W/40 |
|---|------------------|
| Kinematic viscosity at. 100°C, [mm ² /s] | 14.3 |
| Viscosity index | 130 |
| Flash point, [°C] | 225 |
| Pour point, [°C] | -25 |
| Basic number, [mg KOH/g] | 6.0 |

Notice: The above parameter values are typical. The actual values are to be found in the laboratory report attached to each batch of the product.

ADDITIONAL INFORMATION

Chemnaft oils need to be stored in steel or polyethylene containers protecting the product from damp and mechanical impurities. Given the available knowledge, the product does not have an adverse impact on humans, if used properly. Safety information is to be found in the current material safety data sheet.



Chemnaft Sp. z o.o. S.K.A.
Brzeście Nowe 11B/2, 09-130 Baboszewo
NIP 9581664337
www.chemnaft.com