



Qualitium HV 46

Heavy-duty hydraulic oil for vehicles and industrial machinery.



STANDARDS/SPECIFICATIONS

ISO VG 46
ISO 11158 L-HV
DIN 51524 - 3

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Mobil DTE 10 Excel 46	Tellus S2 V 46	Hyspin AWH-M 46
LOTOS	ORLEN OIL	TOTAL
Hydromil L-HV 46	Hydrol L-HV 46	Equivis HV 46

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

APPLICATION

- engineered for hydraulic systems in vehicles and heavy equipment operating in severe conditions
- for hydraulic systems in industrial machinery
- for high pressure and high temperature applications
- for hydraulic systems operating in low ambient temperatures

ADVANTAGES

Ensures excellent efficiency of hydraulic systems, reduces operating costs and increases productivity.

- extends operation even in severe applications
- selected additives enhancing lubricity guarantee excellent anti-wear protection
- demonstrates brilliant anti-oxidation properties and high stability
- exceptional anti-foam properties
- exhibits parameter stability, resists oxidation
- outstanding properties in low temperatures
- optimum demulsibility – guarantees fast release of water
- perfect compatibility with seals

ISO VG	46
Kinematic viscosity at. 40°C (mm ² /s)	46.5
Viscosity index	157
Flash point (COC, °C)	218
Pour point (°C)	-34

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY / TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo
REGON: 365588022, NIP: 7010620854