

HYDRAL L-HV HYDRAULIC OIL/ OLEJ HYDRAULICZNY HYDRAL L-HV

APPLICATION

Hydraulic oil dedicated to heavy-duty operations, with high viscosity index.

ADVANTAGES

- Low susceptibility to foaming
- Very good air separation capacity and demulsifying properties



STANDARDS, SPECIFICATIONS

ISO VG 15, 22, 32, 46, 68, 100, 150

ISO 11158 L-HV

DIN 51 524 cz.3

| Parameters | HYDRAL L-HV HYDRAULIC OIL | | | | | | |
|---|---------------------------|------|------|------|------|-------|-------|
| | 15 | 22 | 32 | 46 | 68 | 100 | 150 |
| Kinematic viscosity at 40°C, [mm ² /s] | 15,3 | 22,5 | 32,5 | 46,1 | 67,9 | 100,2 | 149,6 |
| Viscosity index | 143 | 144 | 145 | 144 | 140 | 135 | 121 |
| Flash point, [°C] | 171 | 192 | 200 | 206 | 220 | 234 | 242 |
| Pour point, [°C] | -39 | -39 | -36 | -33 | -28 | -21 | -18 |
| *Notice: The above parameter values are typical. The actual values are to be found in the laboratory report attached to each batch of the product | | | | | | | |