

QUALITIUM

QUALITIUM HM 15, 22, 32, 46, 68, 100, 150

APPLICATION

Hydraulic oils for operation in extremely difficult conditions (high pressures and temperatures) for highly loaded power transferring, hydraulic driving and control systems.

QUALITIUM HM hydraulic oils may be mixed with and replaced by hydraulic oils from other manufacturers – within the same grade of viscosity and quality.

ADVANTAGES

- Very good filterability and resistance to foaming
- High resistance to oxidation



STANDARDS, SPECIFICATIONS

ISO VG 15, 22, 32, 46, 68, 100, 150

ISO 11158 L-HM

DIN 51 524 cz.2 HLP

Parameters	QUALITIUM HM						
	15	22	32	46	68	100	150
Kinematic viscosity at 40°C, [mm ² /s]	14,9	21,8	32,0	45,9	67,5	98,2	149,1
Viscosity index	125	122	118	115	110	103	100
Flash point, [°C]	178	190	200	209	220	231	239
Pour point, [°C]	-35	-32	-30	-27	-25	-20	-18

*Notice: The above parameter values are typical. The actual values are to be found in the laboratory report attached to each batch of the product

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.