

# QUALITIUM AGRISTOU 10W/40



## SPECIFICATIONS

API: CG-4/CF-4/CF/SF

API: GL-4

ACEA: E3

SAE: 10W/40

ISO: HV

## MEETS REQUIREMENTS

Allison C-4

Case New Holland (CNH) MAT 3525/3526

Caterpillar TO-2

Ford M2C 159B/C, M2C 86B/C, M2C 134D

J.I Case MS-1204/6/7/9

John Deere J27/J20D/J20C

MAN 271

Massey Ferguson M1135/M1139/M1143/  
M1144/M1145

MB 228.1/227.1

New Holland 82009201/2/3

Sperry Vickers/Eaton M2950S/I-280-S

ZF-TE ML 06A/06B/06C/07B

May be used in the following vehicles: AGCO, BELARUS, CASE, CLASS, DEUTZ-FAHR, DRESSER, FENDT, FIAT, HOLDER, HARVESTER, HYUNDAI, JCB, JOHN-DEERE, KUHN, KUBOTA, LAMBORGHINI, LANDINI, MARSHALL, MASSEY-FERGUSON, MITSUBISHI, NEW HOLLAND, PRONAR, RENAULT, STEYER, URSUS, VERMEER, ZETOR and others when oil of this grade is recommended.

## REPLACEMENT OILS

Mobil	Fuchs	Castrol
Agri Extra 10W/40	Agrifarm STOU MC 10W/40	Transmax Agri MP Plus 10W/40
TotalEnergies	Orlen Oil	Shell
Multagri Pro-Tec 10W/40	Agro STOU 10W/40	Spirax S4 TX 10W/40

**Multifunctional oil produced in synthetic technology for agricultural machinery.**

## APPLICATION

- engine oil/gear oil/hydraulic oil for agricultural and construction equipment
- for modern engines in agricultural and construction equipment
- for manual gearboxes operating in severe applications
- hydrokinetic transmissions
- hydraulic systems
- wet clutches and brakes

## ADVANTAGES

***Qualitium Agri STOU 10W/40 produced in synthetic technology guarantees higher cleanliness of the lubrication system by min. 25% - compared to similar oils.***

- guarantees thorough lubrication between interacting components
- one oil for all lubrication systems of modern tractor units reduces the likelihood of making a mistake
- optimum operation of transmissions, clutches and wet brakes
- contains a proper package of additives, which may be applied in systems with Limited Slip requirements
- minimum oil loss results in smaller refills and economy
- excellent anti-foam properties
- exhibits parameter stability, resists oxidation

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	14.5
Viscosity index	145
Flash point (COC, °C)	224
Pour point (°C)	-45

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.