



QUALITIUM AGRI UTTO 10W/30

Multifunctional oil produced in synthetic technology for agricultural machinery.



SPECIFICATIONS

API: GL-4
SAE: 10W/30
PN-ISO 11158 HV
DIN 51 524 cz.3 HVLP

MEETS REQUIREMENTS

Allison C-4
Case New Holland MAT 3505/MAT 3525 (MS1209)
Caterpillar TO-2; Ford ESN-M2C86-B,C
Deutz-Fahr; J.I Case MS-1206, 1207
John Deere JDM J20C
Kubota UDT Fluid; Komatsu
Massey Ferguson CMS M1135, M1141, M1143, M1145
New Holland: M2C 134D (A,B,C)
Sperry Vickers/Eaton M2950S, I-286-S
Volvo VCE 1273.03, WB-101
ZF TE-ML 03E, 05F, 06K, 17E, 21F

May be used in the following vehicles: AGCO, BELARUS, CASE, CLASS, DEUTZ-FAHR, DRESSER, FENDT, FIAT, HOLDER, HARVESTER, HYUNDAI, JCB, JOHN DEERE, KUHN, KUBOTA, LAMBORGHINI, LANDINI, MARSHALL, MASSEY FERGUSON, MITSUBISHI, NEW HOLLAND, PRONAR, RENAULT, STEYER, URSUS, VERMEER, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Mobilfluid 424	Spirax S4 TXM 10W/30	Transmax Agri Trans Plus 80W
LOTOS	ORLEN OIL	FUCHS
Agrol UTTO 10W/30	Platinum Agro UTTO 10W/30	Agrifarm UTTO MP

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

APPLICATION

- gear oil/hydraulic oil for agricultural and construction equipment
- for manual gearboxes operating in severe applications
- hydrokinetic transmissions
- hydraulic systems
- wet clutches and brakes

ADVANTAGES

Qualitium Agri UTTO 10W/30 produced in synthetic technology guarantees higher cleanliness of the lubrication system by min. 25% - compared to similar oils.

- guarantees thorough lubrication between interacting components
- dampens vibrations and squeals made by brakes working unevenly
- optimum operation of transmissions, clutches and wet brakes
- excellent anti-foam properties
- exhibits parameter stability, resists oxidation

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.0
Viscosity index	133
Flash point (COC, °C)	220
Pour point (°C)	-36

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo