



QUALITIUM AGRI UTTO 10W/40

Multifunctional oil produced in synthetic technology for agricultural machinery.



SPECIFICATIONS

API: GL-4
SAE: 10W/40
PN-ISO 11158 HV
DIN 51 524 cz.3 HVLP

MEETS REQUIREMENTS

Allison C-4
Caterpillar TO-2; Deutz-Fahr
Ford ESN-M2C86-B, C
J.I Case MS 1206, 1207
John Deere JDM J20C
Kubota UDT Fluid; Komatsu
Massey Ferguson CMS M1141, M1143, M1145
New Holland: M2C 134D (A,B,C)
Sperry Vickers/Eaton M2950S, I-286-S
Volvo VCE 1273.03, WB-101
ZF TE-ML 03E, 05F, 06K, 17E, 21F

May be used in the following vehicles: AGCO, BELARUS, CASE, CLASS, DEUTZ-FAHR, DRESSER, FENDT, FIAT, HOLDER, HARVESTER, HYUNDAI, JCB, JOHN DEERE, KUHN, KUBOTA, LAMBORGHINI, LANDINI, MARSHALL, MASSEY FERGUSON, MITSUBISHI, NEW HOLLAND, PRONAR, RENAULT, STEYER, URSUS, VERMEER, ZETOR and others when oil of this grade is recommended.

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

APPLICATION

- gear oil/hydraulic oil for agricultural and construction equipment
- for manual gearboxes operating in severe applications
- hydrokinetic transmissions
- hydraulic systems
- wet clutches and brakes

ADVANTAGES

Qualitium Agri UTTO 10W/40 produced in synthetic technology guarantees higher cleanliness of the lubrication system by min. 25% - compared to similar oils.

- guarantees thorough lubrication between interacting components
- minimize the risk of possible malfunction
- optimum operation of transmissions, clutches and wet brakes
- excellent anti-foam properties
- exhibits parameter stability, resists oxidation

| Parameters | Value |
|---|-------|
| Kinematic viscosity at 100°C (mm ² /s) | 14.0 |
| Viscosity index | 140 |
| Flash point (COC, °C) | 220 |
| Pour point (°C) | -36 |

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo