



QUALITIUM AGRI UTTO 10W/40

Multifunctional oil produced in synthetic technology for agricultural machinery.

SPECIFICATIONS

API: GL-4
SAE: 10W/40
PN-ISO 11158 HV
DIN 51 524 cz.3 HVLP

MEETS REQUIREMENTS

Allison C-4
Caterpillar TO-2; Deutz-Fahr
Ford ESN-M2C86-B, C
J.I Case MS 1206, 1207
John Deere JDM J20C
Kubota UDT Fluid; Komatsu
Massey Ferguson CMS M1141, M1143, M1145
New Holland: M2C 134D (A,B,C)
Sperry Vickers/Eaton M2950S, I-286-S
Volvo VCE 1273.03, WB-101
ZF TE-ML 03E, 05F, 06K, 17E, 21F

May be used in the following vehicles: **AGCO, BELARUS, CASE, CLASS, DEUTZ-FAHR, DRESSER, FENDT, FIAT, HOLDER, HARVESTER, HYUNDAI, JCB, JOHN DEERE, KUHN, KUBOTA, LAMBORGHINI, LANDINI, MARSHALL, MASSEY FERGUSON, MITSUBISHI, NEW HOLLAND, PRONAR, RENAULT, STEYER, URSUS, VERMEER, ZETOR** and others when oil of this grade is recommended.

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

APPLICATION

- gear oil/hydraulic oil for agricultural and construction equipment
- for manual gearboxes operating in severe applications
- hydrokinetic transmissions
- hydraulic systems
- wet clutches and brakes

ADVANTAGES

Qualitium Agri UTTO 10W/40 produced in synthetic technology guarantees higher cleanliness of the lubrication system by min. 25% - compared to similar oils.

- guarantees thorough lubrication between interacting components
- minimize the risk of possible malfunction
- optimum operation of transmissions, clutches and wet brakes
- excellent anti-foam properties
- exhibits parameter stability, resists oxidation

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	14.0
Viscosity index	143
Flash point (COC, °C)	225
Pour point (°C)	-38

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date.
Production date and batch number are on the packaging.