

QUALITIUM C3 10W/30

Economical engine oil for passenger cars and light commercial vehicles with DPF particulate filters.



SPECIFICATIONS

SAE: 10W/30
API: SN/SN+
ACEA: C3/C2

QUALITY LEVEL

Mercedes-Benz: 229.31
VW 502.00/505.00/505.01
PSA B712290
Fiat 9.55535-S1

May be used in the following vehicles:
AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

Fully interchangeable and miscible with 5W/30 engine oils with DPF.

The only difference:
10W/30 oil provides a minimum safe start temperature of -30°C.
However 5W/30 oil: -35°C.

Is it worth overpaying in the era of mild winters?

APPLICATION

- passenger cars and light commercial vehicles
- for diesels and petrol engines
- for engines satisfying Euro 6 emission standards and older
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium C3 10W/30 oil is the best solution for economical drivers, who want to provide optimal protection for their car's engine.

- fully compatible with engines with DPF
- **the cheapest on the market in the group of oils dedicated to engines with DPF**
- keeps the engine and the exhaust system perfectly clean
- it perfectly removes solid pollutants, thanks to which it can work freely in extended periods between changes

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.0
Viscosity index	156
Flash point (COC, °C)	235
Pour point (°C)	-38
Total Basic Number (TBN, mg KOH/g)	7.8

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY / TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo

AVAILABLE OIL VOLUMES

4,5L, 60L, 205L