

SPECIFICATIONS

SAE: 10W or 30 API: CF/CF-2

MEETS REQUIREMENTS

Caterpillar TO-4; TO-4M

Allison C-4 API: MT-1

Komatsu KES 07.868.1 ZF TE-ML 03C/07F

May be used in the following vehicles: AGCO, BELARUS, CASE, CLASS, DEUTZ-FAHR, DRESSER, FENDT, FIAT, HOLDER, HARVESTER, HYUNDAI, JCB, JOHN DEERE, KUHN, KUBOTA, LAMBORGHINI, LANDINI, MARSHALL, MASSEY FERGUSON, MITSUBISHI, NEW HOLLAND, PRONAR, RENAULT, STEYER, URSUS, VERMEER, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS Qualitium CAT TO-4 10W

MOBIL	SHELL	CASTROL
MobilTrans	Spirax S4	Transmax
HD 10W	CX 10W	Offroad
		10
LOTOS	ORLEN OIL	TOTAL
Gerax TKD	Platinum	Dynatrans
10W	Multi PTF	ACX
	10W	10W

Qualitium CAT TO-4 30

MOBIL	SHELL	CASTROL
Mobiltrans	Spirax S4	Transmax
HD 30	CX 30	Offroad
		30
LOTOS	ORLEN OIL	TOTAL
Gerax TKD	Platinum	Titan UTTO
30	Multi PTF	TO-4 30
	30	

QUALITIUM CAT TO-4 10W QUALITIUM CAT TO-4 30

<u>Gear oil/hydraulic oil for heavy construction and agricul-tural equipment.</u>



APPLICATION

- Power Transmission Fluid type gear/hydraulic oil for heavy equipment
- for use in gearboxes, also Powershift gearboxes
- for power transmission systems
- hydraulic systems

ADVANTAGES

Qualitium CAT TO-4 10W, 30 oil is the best choice for universal heavy equipment:

- guarantees thorough lubrication between interacting components
- minimum oil loss results in smaller refills and economy
- compatible with currently used elastomers and clutch disc materials
- excellent anti-foam properties
- exhibits parameter stability, resists oxidation

Parameters	Qualitium CAT TO-4	
raiameters	10W	30
Kinematic viscosity at 100°C	5,7	11.6
(mm ² /s)	3,7	11,6
Viscosity index	112	95
Flash point (COC, °C)	225	235
Pour point (°C)	-38	-30

^{*}The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

AVAILABLE OIL VOLUMES

20L, 205L, 1000L

DETAILS OF THE COMPANY/TECHNICAL DEPART-MENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Edit. 2.0/EN - update: 17.01.2022