

# QUALITIUM GEAR ATF III

ATF type oil for automatic transmissions produced in synthetic technology.



## STANDARDS/SPECIFICATIONS

**Dexron IIIH/IIIG/IIIF/IIIE**

Allison C-4; Allison TES-389

Caterpillar TO-2

Ford Mercon

Ford ESP-M2C 138-CJ; M2C 166-H

MAN 339 type V-1/Z-1

MB 236.1, MB 236.2

Voith H55.6336.41/G607

ZF TE-ML 04D/09/11A/14A

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

## REPLACEMENT OILS

Mobil	Fuchs	Castrol
ATF 320	Titan ATF 4000	Transmax ATF DX III Multivehicle
<b>TotalEnergies</b>	<b>Orlen Oil</b>	<b>Shell</b>
Fluide G3 Fluidmatic D3	Gear ATF III	Spirax S3 ATF MD3

## AVAILABLE OIL VOLUMES

1L, 4L, 5L, 20L, 205L, 1000L

## APPLICATION

- for automatic transmissions operating in most severe conditions
- automatic transmissions in passenger cars, commercial vehicles, trucks, buses, agricultural machinery and construction equipment
- power steering devices
- hydrokinetic systems requiring ATF oil
- Powershift gears in tractors and loaders where the manufacturer recommends the use of ATF oil

## ADVANTAGES

**Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.**

- ultimate quality at an excellent price
- guarantees thorough lubrication between interacting components
- properly designed internal friction parameters make the transmission work smoothly
- excellent anti-foam properties
- exhibits parameter stability, resists oxidation in extended periods of operation
- excellent properties in low temperatures make for reduced wear during start-up in winter

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	<b>7.4</b>
Viscosity index	<b>160</b>
Flash point (COC, °C)	<b>218</b>
Pour point (°C)	<b>-48</b>
Color, visual	<b>Red or yellow</b>

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.