



QUALITIUM GEAR GL-4 75W/90

Gear oil produced in synthetic technology for passenger cars, light commercial vehicles, trucks, buses and machines.



SPECIFICATIONS

API: GL-4
SAE: 75W/90

MEETS REQUIREMENTS

Ford WSD-M2C200-C
Mack GO-J
Mack GO-J Plus
MAN 342 M1, M2, M3
MAN 342 S1, S2
Scania STO 1:0
ZF TE-ML 5A, 7A, 8A, 16B-D, 17B

May be used in the following vehicles:
AVIA, CUMMINS, CATERPILLAR,
CASE, CLASS, DEUTZ-FAHR, DAF,
FORD, FIAT, FENDT, GAZ, HYUNDAI,
IKARUS, ISUZU, IVECO, JOHN
DEERE, JCB, KAMAZ, KUBOTA,
KATO, KIA, LEYLAND, LAMBOR-
GHINI, NEW HOLLAND, NEOPLAN,
NEOBUS, NISSAN, MITSUBISHI,
MAZDA, SOLARIS, STEYER, TATRA,
TEREX, TOYOTA, ZETOR and others
when oil of this grade is recom-
mended.

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 205L, 1000L

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
-	Spirax S4 G 75W/90	Syntrans Mul- tivehicle 75W/90
LOTOS	ORLEN OIL	TOTAL
-	-	Traxium Gear 9 FE 75W/90

APPLICATION

- for transmissions operating in severe conditions (at high speed and low torque as well as low speed and high torque)
- transmissions and gearboxes in passenger cars and light commercial vehicles
- transmissions and gearboxes in trucks and buses
- transmissions in machines and equipment e.g. for earth-works, where it is recommended to use oil of such API grade

ADVANTAGES

Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.

- keeps components of transmission clean
- very good anti-wear properties
- brilliantly withdraws heat arising from friction between interacting elements
- considerably reduces vibration and noise

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	16.0
Viscosity index	145
Flash point (COC, °C)	220
Pour point (°C)	-35

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo