



## QUALITIUM GEAR GL-4 85W/140

*Gear oil for passenger cars, light commercial vehicles, trucks, buses and machinery.*



### **SPECIFICATIONS**

API: GL-4

SAE: 85W/140

### **MEETS REQUIREMENTS**

MIL-L-2105 D

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

### **REPLACEMENT OILS**

MOBIL	SHELL	CASTROL
Mobilube GX 140	-	-
LOTOS	ORLEN OIL	FUCHS
-	Hipol GL-4 85W/140	Titan Super-gear 85W/140

### **AVAILABLE OIL VOLUMES**

1L, 5L, 20L, 205L, 1000L

### **APPLICATION**

- gear lubrication - especially gearboxes and main gears
- for used in passenger cars, trucks
- for used in earth moving machines
- designed for vehicles operating in difficult conditions

### **ADVANTAGES**

*Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.*

- very good anti-wear properties
- thanks to its viscosity, clearance is sealed
- brilliantly withdraws heat arising from friction between interacting elements
- considerably reduces vibration and noise

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	27.0
Viscosity index	100
Flash point (COC, °C)	230
Pour point (°C)	-21

\*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

### **DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT**

Qualitium Sp. z o.o.  
Brzeście Nowe 11B/2, 09-130 Baboszewo