



QUALITIUM GEAR GL-4 85W/140

Gear oil for passenger cars, light commercial vehicles, trucks, buses and machinery.

APPLICATION

- gear lubrication - especially gearboxes and main gears
- for used in passenger cars, trucks
- for used in earth moving machines
- designed for vehicles operating in difficult conditions

ADVANTAGES

Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.

- very good anti-wear properties
- thanks to its viscosity, clearance is sealed
- brilliantly withdraws heat arising from friction between interacting elements
- considerably reduces vibration and noise

SPECIFICATIONS

API: GL-4

SAE: 85W/140

MEETS REQUIREMENTS

MIL-L-2105 D

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	25.5
Viscosity index	135
Flash point (COC, °C)	230
Pour point (°C)	-22

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

REPLACEMENT OILS

Mobil	Fuchs	Castrol
Mobilube GX 140	-	-
TotalEnergies	Orlen Oil	Shell
-	Hipol GL-4 85W/140	-

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 205L, 1000L