



QUALITIUM GEAR GL-5 75W/90

Gear oil produced in synthetic technology for passenger cars, light commercial vehicles, trucks, buses and machines.



SPECIFICATIONS

API: GL-5
SAE: 75W/90

MEETS REQUIREMENTS

Ford WSD-M2C200-C
Mack GO-J
Mack GO-J Plus
MAN 342 M1, M2, M3
MAN 342 S1, S2
SAE: J2360
Scania STO 1:0
ZF TE-ML 5A, 7A, 8A, 16B-D, 17B

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 205L, 1000L

REPLACEMENT OILS

| MOBIL | SHELL | CASTROL |
|---------------------------|------------------------------|--------------------------|
| Mobilube HD 75W/90 | Spirax S6 AXME 75W/90 | Syntrax Long Life 75W/90 |
| LOTOS | ORLEN OIL | TOTAL |
| Titanis Super GL-5 75W/90 | Platinum Gear GL-5 SX 75W/90 | Traxium Dual 9 FE 75W/90 |

APPLICATION

- for transmissions operating in most severe conditions (at high speed and low torque as well as low speed and high torque)
- transmissions and gearboxes in passenger cars and light commercial vehicles
- transmissions and gearboxes in trucks and buses
- transmissions in machines and equipment e.g. for earthworks, where it is recommended to use oil of such API grade

ADVANTAGES

Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.

- keeps components of transmission clean
- very good anti-wear properties
- enables easy start-up at low temperatures
- very good thermal stability and resistance to oxidation

| Parameters | Value |
|---|-------------|
| Kinematic viscosity at 100°C (mm ² /s) | 16.0 |
| Viscosity index | 150 |
| Flash point (COC, °C) | 218 |
| Pour point (°C) | -40 |

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo