



## QUALITIUM GEAR GL-5 75W/90

**Gear oil produced in synthetic technology for passenger cars, light commercial vehicles, trucks, buses and machines.**

### **SPECIFICATIONS**

API: GL-5

SAE: 75W/90

### **MEETS REQUIREMENTS**

Ford WSD-M2C200-C

Mack GO-J

Mack GO-J Plus

MAN 342 M1, M2, M3

MAN 342 S1, S2

SAE: J2360

Scania STO 1:0

ZF TE-ML 5A, 7A, 8A, 16B-D, 17B

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

### **REPLACEMENT OILS**

Mobil	Fuchs	Castrol
Mobilube HD 75W/90	Titan Cytrac TD 75W/90	Transmax Axle Long Life 75W/90
TotalEnergies	Orlen Oil	Shell
Traxium Dual 9 FE 75W/90	Gear SX 75W/90 Hipol Semisynthetic GL-5 75W/90	Spirax S6 AXME 75W90

### **AVAILABLE OIL VOLUMES**

1L, 5L, 20L, 205L, 1000L

### **APPLICATION**

- for transmissions operating in most severe conditions (at high speed and low torque as well as low speed and high torque)
- transmissions and gearboxes in passenger cars and light commercial vehicles
- transmissions and gearboxes in trucks and buses
- transmissions in machines and equipment e.g. for earthworks, where it is recommended to use oil of such API grade

### **ADVANTAGES**

***Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.***

- keeps components of transmission clean
- very good anti-wear properties
- enables easy start-up at low temperatures
- very good thermal stability and resistance to oxidation

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	<b>15.2</b>
Viscosity index	<b>165</b>
Flash point (COC, °C)	<b>218</b>
Pour point (°C)	<b>-45</b>

\*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

### **DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT**

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.