



QUALITIUM GEAR GL-5 85W/140

Gear oil for trucks, construction and agricultural machines.



SPECIFICATIONS

API: GL-5

SAE: 85W/140

MEETS REQUIREMENTS

MIL-L-2105 D

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 205L, 1000L

APPLICATION

- intended for use primarily in final drives and rear axles operating in difficult conditions
- designed for trucks, construction and agricultural machines

ADVANTAGES

Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.

- guarantees thorough lubrication between interacting components
- very good protection against corrosion
- exhibits parameter stability, resists oxidation
- very good anti-wear properties

| Parameters | Value |
|---|-------|
| Kinematic viscosity at 100°C (mm ² /s) | 26.2 |
| Viscosity index | 95 |
| Flash point (COC, °C) | 238 |
| Pour point (°C) | -22 |

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo