



QUALITIUM GEAR GL-5 85W/140

Gear oil for trucks, construction and agricultural machines.

SPECIFICATIONS

API: GL-5

SAE: 85W/140

MEETS REQUIREMENTS

MIL-L-2105 D

May be used in the following vehicles:
AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Fuchs	Castrol
Mobilube HD 85W/140	Titan Supergear 85W/140	Syntrans Axle EPX 85W/140
TotalEnergies	Orlen Oil	Shell
Traxium Axle 7 85W/140	Gear LX 85W/140 Hipol GL-5 85W/140	Spirax S3 AX 85W/140 Spirax S2 A 85W/140

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 205L, 1000L

APPLICATION

- intended for use primarily in final drives and rear axles operating in difficult conditions
- designed for trucks, construction and agricultural machines

ADVANTAGES

Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.

- guarantees thorough lubrication between interacting components
- very good protection against corrosion
- exhibits parameter stability, resists oxidation
- very good anti-wear properties

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	26.2
Viscosity index	136
Flash point (COC, °C)	230
Pour point (°C)	-24

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date.

Production date and batch number are on the packaging.