



QUALITIUM GEAR GL-5 85W/90

Gear oil for passenger cars, light commercial vehicles, trucks and buses.



SPECIFICATIONS

API: GL-5

SAE: 85W/90

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, DAF, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, IVECO, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 205L, 1000L

APPLICATION

- transmissions and rear axles operating in difficult conditions (at high speed and low torque as well as low speed and high torque)
- transmissions and manual gearboxes in passenger cars, off-road vehicles and light commercial vehicles
- transmissions and manual gearboxes in trucks and buses, where it is recommended to use oil of such API grade

ADVANTAGES

Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.

- guarantees thorough lubrication between interacting components
- very good protection against corrosion
- exhibits parameter stability, resists oxidation
- very good anti-wear properties

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	16.4
Viscosity index	115
Flash point (COC, °C)	224
Pour point (°C)	-30

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo