



# QUALITIUM MOTO 4T 15W/40

Mineral motor oil for motorcycles.



## STANDARDS/SPECIFICATIONS

SAE: 15W/40

API: SL/SJ

JASO MA-2

JASO T903

May be used in motorcycles:  
**BMW, DUCATI, HONDA, KAWASAKI, SUZUKI, YAMAHA** and others when oil of this grade is recommended.

## AVAILABLE OIL VOLUMES

1L, 5L, 20L, 60L, 205L

## APPLICATION

- four-stroke engines of sport, cruiser and touring motorcycles, as well as quads
- performs brilliantly in motorcycle transmissions and wet clutch transmissions

## ADVANTAGES

- ensures excellent engine protection – extending its life to a maximum
- very good anti-wear properties
- prevents sedimentation by keeping the deposits in a suspended matter
- demonstrates very good oxidation resistance

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	14.2
Viscosity index	133
Flash point (COC, °C)	220
Pour point (°C)	-27

\*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo