



## QUALITIUM MOTO 4T 15W/40

Mineral motor oil for motorcycles.

### **STANDARDS/SPECIFICATIONS**

SAE: 15W/40

API: SL/SJ

JASO MA-2

JASO T903

### **AVAILABLE OIL VOLUMES**

1L, 5L, 20L, 60L, 205L

### **APPLICATION**

- four-stroke engines of sport, cruiser and touring motorcycles, as well as quads
- performs brilliantly in motorcycle transmissions and wet clutch transmissions

### **ADVANTAGES**

- ensures excellent engine protection – extending its life to a maximum
- very good anti-wear properties
- prevents sedimentation by keeping the deposits in a suspended matter
- demonstrates very good oxidation resistance

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	14.5
Viscosity index	140
Flash point (COC, °C)	220
Pour point (°C)	-30

\*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

### **DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT**

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.