

# QUALITIUM POWER 0W/20

Synthetic motor oil for passenger cars and light commercial vehicles.



## SPECIFICATIONS

SAE: 0W/20

API: SP

ACEA: C2

## MEETS REQUIREMENTS

ILSAC GF-6A

API: SN/SM/CF

May be used in the following vehicles:

AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

## REPLACEMENT OILS

MOBIL	SHELL	Texaco
Mobil 1 0W/20	-	Havoline Ultra 0W/20
Lotos	Orlen Oil	Motul
Quazar Dynamic DX 0W/20	Platinum Pro 0W/20	8100 Eco LITE 0W/20

## AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L

## APPLICATION

- passenger cars and light commercial vehicles
- for petrol and diesels engines
- for engines satisfying Euro 6 emission standards
- engines equipped with DPF/FAP filters as well as three-way catalytic converter (TWC)

## ADVANTAGES

*Qualitium Power 0W/20 is the perfect combination of energy efficiency with optimal lubrication.*

- allows to develop maximum power of the engine at low and high temperatures
- ideal protection against wear of the timing chain
- protection against Low Speed Pre-Ignition (LSPI)
- perfectly removes solid impurities and reduces the formation of deposits on the pistons and the turbocharger

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	8.9
Viscosity index	163
Flash point (COC, °C)	220
Pour point (°C)	-40
Total Basic Number (TBN, mg KOH/g)	7.5

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo