

QUALITIUM POWER 0W/20

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 0W/20

API: SP

ACEA: C2

MEETS REQUIREMENTS

ILSAC GF-6A

API: SN/SM/CF

May be used in the following vehicles:
AUDI, BMW, CHEVROLET, CHRYSLER,
CITROEN, DACIA, DAEWOO, FIAT, FORD,
HONDA, HYUNDAI, KIA, ŁADA, MAZDA,
MERCEDES, MITSUBISHI, NISSAN, OPEL,
PEUGEOT, RENAULT, ROVER, SAAB,
SEAT, SKODA, SUBARU, SUZUKI,
TOYOTA, VOLKSWAGEN, VOLVO and others
when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
Mobil 1 0W/20	Helix Ultra 0W/20	Magnatec Hy- brid 0W/20
Elf/To- talEnergies	Orlen Oil	Texaco
Quartz 9000 Future GF-6 0W/20	Platinum Pro 0W/20	Havoline ProDS 0W/20

AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L

APPLICATION

- passenger cars and light commercial vehicles
- for petrol and diesels engines
- for engines satisfying Euro 6 emission standards
- engines equipped with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium Power 0W/20 is the perfect combination of energy efficiency with optimal lubrication.

- allows to develop maximum power of the engine at low and high temperatures
- ideal protection against wear of the timing chain
- protection against Low Speed Pre-Ignition (LSPI)
- perfectly removes solid impurities and reduces the formation of deposits on the pistons and the turbocharger

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	8.1
Viscosity index	165
Flash point (COC, °C)	218
Pour point (°C)	-48
Total Basic Number (TBN, mg KOH/g)	7.5

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.