



QUALITIUM POWER 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 5W/30

API: SP/SN/SN+

ACEA: C3/C2

VW 502.00/505.00/505.01

Mercedes-Benz: 229.31

BMW: Longlife-04

GM Dexos 2

Fiat 9.55535-S3

Stellantis FPW 9.55535/03

Opel OVO401547

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

| Mobil | Shell | Castrol |
|--|---|---|
| Mobil 1 ESP Formula P 5W/30; Mobil Super 3000 XE 5W/30 | Helix Ultra ECT C3 5W/30; Helix HX7 Professional AV 5W/30 | EDGE 5W-30 C3; Edge 5W/30 M; Magnatec 5W/30 C3 |
| Elf/TotalEnergies | Orlen Oil | Texaco |
| Evolution Full-Tech MSX 5W/30; Quartz Ineo MDC 5W/30 | Max Expert XD 5W/30; Lotos Aurum C3 5W/30 | Havoline ProDS M 5W/30; Havoline ProDS BM 5W/30 |

APPLICATION

- passenger cars and light commercial vehicles
- for petrol and diesels engines
- for engines satisfying Euro 6 emission standards
- engines equipped with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium Power 5W/30 oil protects particulate filters to the max, prolonging their life by reducing deposition of pollutants.

- allows to reach the maximum engine power at low and high temperatures
- keeps the engine and the exhaust system perfectly clean
- perfectly removes solid pollutants from the engine which it can work freely in extended oil change intervals

| Parameters | Value |
|--------------------------------------|-------------|
| Kinematic viscosity at 100°C (mm²/s) | 11.4 |
| Viscosity index | 158 |
| Flash point (COC, °C) | 215 |
| Pour point (°C) | -39 |
| Total Basic Number (TBN, mg KOH/g) | 7.9 |

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

AVAILABLE OIL VOLUMES

1L, 4L, 5L, 20L, 60L, 205L, 1000L

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo