

# QUALITIUM POWER 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles.



## SPECIFICATIONS

SAE: 5W/30  
API: SN/SN+  
ACEA: C3/C2

## MEETS REQUIREMENTS

**VW 502.00/505.00/505.01**  
Mercedes-Benz: 229.31  
BMW: Longlife-04  
GM Dexos 2

May be used in the following vehicles:  
**AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO** and others when oil of this grade is recommended.

## REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Mobil Super 3000 XE 5W/30	Helix HX8 ECT C3 5W/30	Castrol EDGE 5W/30 C3
LOTOS	ORLEN OIL	ELF
Lotos Aurum C3 Lotos Quazar K 5W/30	Platinum Pro XD 5W/30	Evolution Full-Tech MSX 5W/30

## AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L

## APPLICATION

- passenger cars and light commercial vehicles
- for petrol and diesels engines
- for engines satisfying Euro 6 emission standards
- engines equipped with DPF/FAP filters as well as three-way catalytic converter (TWC)

## ADVANTAGES

*Qualitium Power 5W/30 oil protects particulate filters to the max, prolonging their life by reducing deposition of pollutants.*

- allows to reach the maximum engine power at low and high temperatures
- keeps the engine and the exhaust system perfectly clean
- perfectly removes solid pollutants from the engine which it can work freely in extended oil change intervals

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	<b>11.0</b>
Viscosity index	<b>163</b>
Flash point (COC, °C)	<b>230</b>
Pour point (°C)	<b>-38</b>
Total Basic Number (TBN, mg KOH/g)	<b>7.5</b>

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.  
Brzeście Nowe 11B/2, 09-130 Baboszewo