



QUALITIUM POWER 5W/40

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 5W/40

API: SP/SN/SN+

ACEA: C3/C2

MEETS REQUIREMENTS

VW 502.00/505.00/505.01

Mercedes-Benz: 229.31/229.51

BMW: Longlife-04

GM Dexos 2

GM-LL-A025/GM-LL-B025

Fiat 9.55535-S2

Ford WSS-M2C-917-A

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
-	Helix HX8 ECT C3 5W/40; Helix XH7 ECT 5W/40	EDGE 5W/40; Magnatec 5W/40 C3
Elf/TotalEnergies	Orlen Oil	Texaco
Quartz Ineo C3 5W/40	Max Expert C3 5W/40; Lotos Aurum C3 5W/40	Havoline Ultra S 5W/40

AVAILABLE OIL VOLUMES

1L, 4L, 5L, 20L, 60L, 205L, 1000L

APPLICATION

- passenger cars and light commercial vehicles
- for petrol engines and diesels
- for engines satisfying Euro 6 emission standards
- engines equipped with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium Power 5W/40 oil protects particulate filters to the max, prolonging their life by reducing deposition of pollutants.

- allows to reach the maximum engine power at low and high temperatures
- keeps the engine and the exhaust system perfectly clean
- perfectly removes solid pollutants from the engine which it can work freely in extended oil change intervals

Parameters	Value
Kinematic viscosity at. 100°C (mm ² /s)	14.5
Viscosity index	160
Flash point (COC, °C)	228
Pour point (°C)	-39
Total Basic Number (TBN, mg KOH/g)	7.9

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.