

# QUALITIUM POWER P 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles designed for Peugeot, Citroen and Renault cars.



## SPECIFICATIONS

SAE: 5W/30  
API: SN/SN+  
ACEA: C2

## MEETS REQUIREMENTS

PSA B71 2290  
RN 0700  
GM Dexos 2

May be used in the following vehicles:  
**AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN,** and others when oil of this grade is recommended.

## REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Mobil 1 ESP Formula 5W/30	Helix Ultra Professional AP-L 5W/30	Castrol Magnatec Stop-Start 5W/30 C2
LOTOS	ORLEN OIL	ELF
Lotos Quazar C2+C3 5W/30	Platinum Max Expert XF 5W/30	Evolution Full-Tech FE 5W/30

## AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L

## APPLICATION

- passenger cars and light commercial vehicles
- for diesels and petrol engines
- designed for users of Peugeot, Citroen and Renault cars
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

## ADVANTAGES

*Qualitium Power P 5W/30 meets the strictest standards and specifications.*

- allows to reach the maximum engine power at low and high temperatures
- influences the reduction of emissions, which protects the natural environment
- keeps the engine and exhaust system extremely clean
- perfectly removes solid pollutants from the engine which it can work freely in extended oil change intervals

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	11.0
Viscosity index	166
Flash point (COC, °C)	228
Pour point (°C)	-42
Total Basic Number (TBN, mg KOH/g)	7.9

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.  
Brzeście Nowe 11B/2, 09-130 Baboszewo