

SPECIFICATIONS SAE: 5W/30 API: SP/SN/SN+ ACEA: C2

#### PSA B71 2290

RN 0700/RN 0710 GM Dexos 2 Fiat 9.55535-S1

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAE-WOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, and others when oil of this grade is recommended.

#### **REPLACEMENT OILS**

Mobil	Shell	Castrol
Super 3000	Helix Ultra	Edge 5W/30
XE 5W/30	Professional	C3;
	AP-L 5W/30;	Magnatec
	Helix Ultra ECT	5W/30 P;
	C3 5W/30	GTX 5W/30
		C2
Elf/TotalE-	Orlen Oil	Texaco
nergies		
Evolution	Max Expert XF	Havoline En-
Full-Tech C2	5W/30	ergy MS
5W/30;		5W/30
Elf Evolution		
Full-Tech FE		
5W/30;		
Quartz Ineo		
ECS 5W/30		

*AVAILABLE OIL VOLUMES* 1L, 4L, 5L, 20L, 60L, 205L, 1000L

# QUALITIUM POWER P 5W/30

<u>Synthetic motor oil for passenger cars and light com-</u> <u>mercial vehicles designed for Peugeot, Citroen and</u> <u>Renault cars.</u>



### **APPLICATION**

- passenger cars and light commercial vehicles
- for diesels and petrol engines
- designed for users of Peugeot, Citroen and Renault cars
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

## **ADVANTAGES**

# *Qualitium Power P 5W/30 meets the strictest standards and specifications.*

- allows to reach the maximum engine power at low and high temperatures

- influences the reduction of emissions, which protects the natural environment

- keeps the engine and exhaust system extremely clean

- perfectly removes solid pollutants from the engine which it can work freely in extended oil change intervals

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	11.3
Viscosity index	158
Flash point (COC, °C)	218
Pour point (°C)	-39
Total Basic Number (TBN, mg KOH/g)	8.3

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

#### DETAILS OF THE COMPANY/TECHNICAL DEPART-MENT

Qualitium Sp. z o.o. Brzeście Nowe 11B/2, 09-130 Baboszewo