



QUALITIUM POWER P 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles designed for Peugeot, Citroen and Renault cars.



SPECIFICATIONS

SAE: 5W/30

API: SP/SN/SN+

ACEA: C2

MEETS REQUIREMENTS

PSA B71 2290

RN 0700/RN 0710

GM Dexos 2

Fiat 9.55535-S1

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, LADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
Super 3000 XE 5W/30	Helix Ultra Professional AP-L 5W/30; Helix Ultra ECT C3 5W/30	Edge 5W/30 C3; Magnatec 5W/30 P; GTX 5W/30 C2
Elf/TotalEnergies	Orlen Oil	Texaco
Evolution Full-Tech C2 5W/30; Elf Evolution Full-Tech FE 5W/30; Quartz Ineo ECS 5W/30	Max Expert XF 5W/30	Havoline En- ergy MS 5W/30

APPLICATION

- passenger cars and light commercial vehicles
- for diesels and petrol engines
- designed for users of Peugeot, Citroen and Renault cars
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium Power P 5W/30 meets the strictest standards and specifications.

- allows to reach the maximum engine power at low and high temperatures
- influences the reduction of emissions, which protects the natural environment
- keeps the engine and exhaust system extremely clean
- perfectly removes solid pollutants from the engine which it can work freely in extended oil change intervals

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.3
Viscosity index	161
Flash point (COC, °C)	220
Pour point (°C)	-39
Total Basic Number (TBN, mg KOH/g)	8.2

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.

AVAILABLE OIL VOLUMES

1L, 4L, 5L, 20L, 60L, 205L, 1000L