

QUALITIUM POWER V 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 5W/30
API: SN/SM/CF
ACEA: C3

MEETS REQUIREMENTS

Volkswagen: 504.00/507.00

(meets the requirements of standards 502.00/505.00/505.01)

BMW: Longlife-04

GM Dexos 2

Mercedes-Benz: 229.31/229.51

Porsche: C30

May be used in the following vehicles:
AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Mobil 1 ESP Formula 5W/30	Helix Ultra ECT C3 5W/30 Helix HX7 Professional AV 5W/30	Castrol EDGE 5W/30 LL
LOTOS	ORLEN OIL	ELF
Lotos Aurum 504/507 5W/30	Platinum Max Expert V 5W/30	Evolution Full-Tech LLX 5W/30

APPLICATION

- passenger cars and light commercial vehicles
- for diesels and petrol engines
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)
- extended oil drain intervals (meets VW 504/507)

ADVANTAGES

Qualitium Power V 5W/30 oil protects particulate filters to the max, prolonging their life by reducing deposition of pollutants.

- allows to reach the maximum engine power at low and high temperatures
- keeps the engine and the exhaust system perfectly clean
- ensures high stability of parameters at extended oil drain intervals

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.5
Viscosity index	160
Flash point (COC, °C)	235
Pour point (°C)	-38
Total Basic Number (TBN, mg KOH/g)	7.0

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo

AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L