

# QUALITUM POWER V 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles.



## SPECIFICATIONS

SAE: 5W/30

API: SN/SM/CF

ACEA: C3

## MEETS REQUIREMENTS

**Volkswagen: 504.00/507.00**

(meets the requirements of standards 502.00/505.00/505.01)

Mercedes-Benz:

229.31/229.51/229.52

Fiat 9.55535-S3

Porsche: C30

BMW: Longlife-04

GM Dexos 2

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

## REPLACEMENT OILS

Mobil	Shell	Castrol
Mobil 1 ESP 5W/30 Super 3000 Formula V 5W/30	Helix Ultra ECT 5W/30 Helix HX7 Professional AV 5W/30 Helix HX8 5W/30	Edge 5W/30 LL GTX 5W/30 C3
Elf/TotalEnergies	Orlen Oil	Texaco
Evolution Full-Tech LLX 5W/30 Quartz Ineo Longlife 5W/30	Max Expert V 5W/30; Lotos Synthetic 504/507 5W/30	Havoline ProDS V 5W/30

## APPLICATION

- passenger cars and light commercial vehicles
- for diesels and petrol engines
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)
- extended oil drain intervals (meets VW 504/507)

## ADVANTAGES

*Qualitium Power V 5W/30 oil protects particulate filters to the max, prolonging their life by reducing deposition of pollutants.*

- allows to reach the maximum engine power at low and high temperatures
- keeps the engine and the exhaust system perfectly clean
- ensures high stability of parameters at extended oil drain intervals

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	11.4
Viscosity index	164
Flash point (COC, °C)	218
Pour point (°C)	-39
Total Basic Number (TBN, mg KOH/g)	7.9

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## AVAILABLE OIL VOLUMES

1L, 4L, 5L, 20L, 60L, 205L, 1000L

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.