

QUALITIUM PROTEC 10W/40

Semisynthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 10W/40

API: SL/SJ/CF

ACEA: A3/B3; A3/B4

MEETS REQUIREMENTS

Mercedes-Benz: 229.1

Volkswagen: 505.00

May be used in the following vehicles:

AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Super 2000 X1 10W/40	Helix HX 7 10W/40	Magnatec 10W/40
LOTOS	ORLEN OIL	ELF
Semisynthetic 10W/40	Platinum Sem- isynthetic 10W/40	Evolution 700 STI 10W/40

AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L

APPLICATION

- passenger cars and light commercial vehicles
- for diesels and high performance petrol engines
- may be used in cars running on LPG
- engines (turbocharged or not, with or without a catalyst)
- engines with extended oil drain intervals - where indicated by engine manufacturers
- worn-out engines

ADVANTAGES

Qualitium Protec 10W/40 guarantees lower oil consumption even by 20% in comparison to corresponding oils.

- ensures excellent engine protection – extending its life to a maximum
- reduces fuel consumption
- demonstrates resistance to oxidation in all operating conditions
- reduces loss of oil in older engine models

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	14.5
Viscosity index	150
Flash point (COC, °C)	218
Pour point (°C)	-36
Total Basic Number (TBN, mg KOH/g)	10.3

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo