

QUALITIUM PROTEC 15W/40

Mineral multi-grade motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 15W/40

API: SL/SJ/CF

ACEA: A3/B3, A3/B4

MEETS REQUIREMENTS

Mercedes-Benz: 229.1

Volkswagen: 505.00

May be used in the following vehicles:
AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Mobil Super 1000 X1 15W/40 Mobil Super 1000 X1 Diesel 15W/40	Helix HX5 15W/40	Castrol GTX 15W/40 A3/B3
LOTOS	ORLEN OIL	ELF
Mineralny 15W/40	Platinum Classic Mineral 15W/40	Sporti TXI 15W/40

APPLICATION

- passenger cars and light commercial vehicles
- for petrol engines and diesels (without DPFs)
- engines (turbocharged or not, with or without a catalyst)
- may be used in cars running on LPG
- modern engines
- ideal for older high mileage engine models

ADVANTAGES

Qualitium Protec 15W/40 guarantees lower oil consumption even by 20% in comparison to corresponding oils.

- protects engine elements from seizing
- ensures easy start-up of the engine at low temperatures
- effectively neutralizes acids arising from fuel combustion
- demonstrates perfect resistance to oxidation even in severe operating conditions
- minimizes oil leaks in worn-out engines

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	14.7
Viscosity index	136
Flash point (COC, °C)	216
Pour point (°C)	-33
Total Basic Number (TBN, mg KOH/g)	10.2

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

AVAILABLE OIL VOLUMES

1L, 5L, 60L, 205L, 1000L