



QUALITIUM TRUCK EVO 5W/30

Low ash engine oil for trucks increasing fuel economy.



SPECIFICATIONS

SAE: 5W/30

API: CJ-4/CI-4

ACEA: E6/E7/E9

MEETS REQUIREMENTS

Caterpillar ECF-3

Cummins CES 20081

Deutz DQC-IV-10 LA

Mack EO-O Premium Plus

MAN M 3677

MB 228.51

MTU Type 3.1

Renault RVI RLD-3

Volvo VDS-4

DAF, Iveco, Scania

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Delvac XHP Ultra 5W/30	Rimula R6 LME 5W/30	Vecton Fuel Saver 5W/30 E6/E9
LOTOS	ORLEN OIL	TOTAL
Turdus Powertec 5100 FE 5W/30	Platinum Ul-tor Perfect 5W/30	Rubia TIR 9900 FE 5W/30

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

APPLICATION

- trucks, buses, agricultural machinery and construction equipment
- for Diesel engines satisfying Euro 5 and Euro 6 emission standards
- engines with diesel particulate filters (DPFs)
- with exhaust gas recirculation (EGR) or selective catalytic reduction (SCR) systems (vehicles using Ad-blue)
- may be used in passenger cars
- ideal for companies with a varied fleet comprising trucks, commercial vehicles, passenger cars and heavy equipment

ADVANTAGES

Ensures ideal anti-wear protection, reduces wear of engine elements by at least 15% in comparison to corresponding oils.

- fuel-economy oil – ensures fuel economy during operation
- very good qualities at low temperatures in severe winter conditions
- good flow of oil in extremely low temperatures
- keeps pistons and other engine elements clean
- enables making the most of the engine power
- brilliantly deals with contaminants, which is why it may be used in severe operating environments, e.g. quarries, construction sites

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.5
Viscosity index	158
Flash point (COC, °C)	216
Pour point (°C)	-40
Total Basic Number (TBN, mg KOH/g)	10.2
Sulphate ash (%)	0.95

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo