



QUALITIUM TRUCK PLUS 15W/40 (SHPD)

Motor oil for trucks and buses.

SPECIFICATIONS

SAE: 15W/40

API: CI-4/CH-4/CG-4/CF

API: SL

ACEA: E4/E7; A3/B3/B4

MEETS REQUIREMENTS

Caterpillar ECF-1a

Cummins CES 20071/72/75/76/77

Deutz DQC-III-05

Mack EO-M Plus, Mack EO-N

MAN M 3275-1

MB 228.3

MTU Type 2

Renault RVI RLD2

Volvo VDS-2, VDS-3

DAF, Iveco, Scania

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Fuchs	Castrol
Delvac Modern 15W-40 Super Defense V4	Titan Truck Plus 15W/40	CRB Multi 15W/40 CI-4/E7
TotalEnergies	Orlen Oil	Shell
Rubia TIR 7400 15W/40	Ultor Plus 15W/40	Rimula R4 X 15W/40

APPLICATION

- trucks, buses, agricultural machinery and construction equipment
- for Diesel engines satisfying Euro 5 emission standards
- with exhaust gas recirculation (EGR) or selective catalytic reduction (SCR) systems (vehicles using Ad-blue)
- for earlier engine models compliant with Euro 2,3,4
- may be used in passenger cars powered by Diesel and petrol engines

ADVANTAGES

Ensures ideal anti-wear protection, reduces wear of engine elements by at least 15% in comparison to corresponding oils.

- stable and high quality of oil at an excellent price
- keeps pistons and other engine elements clean
- extends operation
- enables making the most of the engine power
- brilliantly deals with contaminants, which is why it may be used in severe operating environments, e.g. quarries, construction sites
- excellent lubrication of older engine models, used in both road machinery and elsewhere

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	14.6
Viscosity index	147
Flash point (COC, °C)	225
Pour point (°C)	-36
Total Basic Number (TBN, mg KOH/g)	12.1
Sulphate ash (%)	1.5

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.