

SPECIFICATIONS

SAE: 15W/40 API: CG-4/CF-4/CF

API: SL

ACEA: E3; A3/B3

MEETS REQUIREMENTS

MAN 3275 MB 228.1 Volvo VDS-2 MTU Cat 1

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

| MOBIL | SHELL | FUCHS |
|--------------|--------------|--------------|
| Delvac Super | - | Titan |
| 1400 | | Universal HD |
| 15W/40 | | 15W/40 |
| LOTOS | ORLEN | TOTAL |
| | OIL | |
| Turdus MD | Platinum | Rubia 4400 |
| 15W/40 | Ultor Diesel | 15W/40 |
| | 15W/40 | |

AVAILABLE OIL VOLUMES 5L, 20L, 205L, 1000L

QUALITIUM TRUCK SPECIAL 15W/40

Motor oil for trucks and buses



APPLICATION

- trucks, buses, agricultural machinery and construction equipment
- for Diesel engines satisfying Euro 4,3,2,1 emission standards
- may be used in passenger cars powered by Diesel and petrol engines
- ideal for companies with a varied fleet comprising trucks, commercial vehicles, passenger cars and heavy equipment

ADVANTAGES

Ensures ideal anti-wear protection, reduces wear of engine elements by at least 15% in comparison to corresponding oils.

- stable and high quality of oil at an excellent price
- keeps pistons and other engine elements clean
- brilliantly deals with contaminants, which is why it may be used in severe operating environments, e.g. quarries, construction sites
- excellent lubrication of older engine models, used in both road machinery and elsewhere
- makes older seals swell preventing oil leaks

| Parameters | Value |
|---|-------|
| Kinematic viscosity at 100°C (mm ² /s) | 14.1 |
| Viscosity index | 130 |
| Flash point (COC, °C) | 226 |
| Pour point (°C) | -27 |
| Total Basic Number (TBN, mg KOH/g) | 10.0 |
| Sulphate ash (%) | 1.4 |

^{*} The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o. Brzeście Nowe 11B/2, 09-130 Baboszewo

Edit. 2.0/EN - update: 13.12.2021