



QUALITIUM TRUCK SPECIAL 15W/40

Motor oil for trucks and buses

SPECIFICATIONS

SAE: 15W/40

API: CG-4/CF-4/CF

API: SL

ACEA: E3; A3/B3

MEETS REQUIREMENTS

MAN 3275

MB 228.1

Volvo VDS-2

MTU Cat 1

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Fuchs	Castrol
-	Titan Universal HD 15W/40	-
TotalEnergies	Orlen Oil	Shell
Rubia 4400 15W/40	Ultor Diesel 15W/40	Rimula R2 Extra 15W/40

APPLICATION

- trucks, buses, agricultural machinery and construction equipment
- for Diesel engines satisfying Euro 4,3,2,1 emission standards
- may be used in passenger cars powered by Diesel and petrol engines
- ideal for companies with a varied fleet comprising trucks, commercial vehicles, passenger cars and heavy equipment

ADVANTAGES

Ensures ideal anti-wear protection, reduces wear of engine elements by at least 15% in comparison to corresponding oils.

- stable and high quality of oil at an excellent price
- keeps pistons and other engine elements clean
- brilliantly deals with contaminants, which is why it may be used in severe operating environments, e.g. quarries, construction sites
- excellent lubrication of older engine models, used in both road machinery and elsewhere
- makes older seals swell preventing oil leaks

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	14.8
Viscosity index	135
Flash point (COC, °C)	226
Pour point (°C)	-33
Total Basic Number (TBN, mg KOH/g)	9.5
Sulphate ash (%)	1.7

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date.
Production date and batch number are on the packaging.