



QUALITIUM TRUCK SUPER 10W/40 (UHPD)

Semisynthetic motor oil for trucks.



SPECIFICATIONS

SAE: 10W/40
API: CI-4/CH-4/CG-4/CF
API: SL
ACEA: E4/E7

MEETS REQUIREMENTS

Caterpillar ECF-1a
Cummins CES 20076/77
Deutz DQC-III-10
Mack EO-N
MAN M 3277, M 3275
MB 228.5
MTU Type 2
Renault RVI RLD2
Scania LDF-2
Volvo VDS-3, VDS-2
DAF, Iveco

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

MOBIL	SHELL	CASTROL
Delvac XHP Extra 10W/40	Rimula R5 LE 10W/40	Vecton Long Drain 10W/40 E7
LOTOS	ORLEN OIL	TOTAL
Turdus Power-tec 3000 10W/40	Platinum Ul-tor Extreme 10W/40	Rubia TIR 8600 10W/40

APPLICATION

- trucks, buses, agricultural machinery and construction equipment
- for Diesel engines satisfying Euro 5 emission standards
- with exhaust gas recirculation (EGR) or selective catalytic reduction (SCR) systems (vehicles using Ad-blue)
- may be used in passenger cars powered by Diesel and petrol engines

ADVANTAGES

Ensures ideal anti-wear protection, reduces wear of engine elements by at least 15% in comparison to corresponding oils.

- good flow of oil in extremely low temperatures
- keeps pistons and other engine elements clean
- extends operation
- enables making the most of the engine power
- brilliantly deals with contaminants, which is why it may be used in severe operating environments, e.g. quarries, construction sites

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	14.0
Viscosity index	152
Flash point (COC, °C)	240
Pour point (°C)	-31
Total Basic Number (TBN, mg KOH/g)	12.0
Sulphate ash (%)	1.3

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L