



QUALITIUM TRUCK SUPER 10W/40 (UHPD)

Semisynthetic motor oil for trucks.

SPECIFICATIONS

SAE: 10W/40
API: CI-4/CH-4/CG-4/CF
API: SL
ACEA: E4/E7

MEETS REQUIREMENTS

Caterpillar ECF-1a
Cummins CES 20076/77
Deutz DQC-III-10
Mack EO-N
MAN M 3277, M 3275
MB 228.5
MTU Type 2
Renault RVI RLD2
Scania LDF-2
Volvo VDS-3, VDS-2
DAF, Iveco

May be used in the following vehicles: AVIA, CUMMINS, CATERPILLAR, CASE, CLASS, DEUTZ-FAHR, FORD, FIAT, FENDT, GAZ, HYUNDAI, IKARUS, ISUZU, JOHN DEERE, JCB, KAMAZ, KUBOTA, KATO, KIA, LEYLAND, LAMBORGHINI, NEW HOLLAND, NEOPLAN, NEOBUS, NISSAN, MITSUBISHI, MAZDA, SOLARIS, STEYER, TATRA, TEREX, TOYOTA, ZETOR and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Fuchs	Castrol
Delvac Modern 10W-40 Super Defense	Titan Cargo MC 10W/40 Titan Unimax Ultra MC 10W/40	Vecton Long Drain 10W/40 E7
TotalEnergies	Orlen Oil	Shell
Rubia TIR 8600 10W/40	Ultor Extreme 10W/40 Ultor Master 10W/40	Rimula R5 E 10W/40

APPLICATION

- trucks, buses, agricultural machinery and construction equipment
- for Diesel engines satisfying Euro 5 emission standards
- with exhaust gas recirculation (EGR) or selective catalytic reduction (SCR) systems (vehicles using Ad-blue)
- may be used in passenger cars powered by Diesel and petrol engines

ADVANTAGES

Ensures ideal anti-wear protection, reduces wear of engine elements by at least 15% in comparison to corresponding oils.

- good flow of oil in extremely low temperatures
- keeps pistons and other engine elements clean
- extends operation
- enables making the most of the engine power
- brilliantly deals with contaminants, which is why it may be used in severe operating environments, e.g. quarries, construction sites

Parameters	Value
Kinematic viscosity at. 100°C (mm ² /s)	14.4
Viscosity index	152
Flash point (COC, °C)	224
Pour point (°C)	-33
Total Basic Number (TBN, mg KOH/g)	12.2
Sulphate ash (%)	1.3

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

AVAILABLE OIL VOLUMES

5L, 20L, 205L, 1000L

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.
Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.