



## SPECIFICATIONS

SAE: 0W/30

API: SN/CF

ACEA: C2

## MEETS REQUIREMENTS

FORD WSS-M2C950-A

JAGUAR LAND ROVER STJLR.03.5007

FIAT 9.55535-GS1/DS1

Honda, Jeep, Mitsubishi

Subaru, Suzuki, Toyota

May be used in the following vehicles:

AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MERCEDES, MITSUBISHI, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

## REPLACEMENT OILS

Castrol Magnatec Stop-Start 0W/30 D

Total Quartz Ineo FDE 0W/30

Motul 8100 Eco Clean C2 0W/30

Valvoline SynPower DT C2 0W/30

Platinum Max Expert 0W/30

Lotos Quazar Dynamic c2 0W/30

## AVAILABLE OIL VOLUMES

1L, 4L, 20L, 60L, 205L, 1000L

# QUALITIUM POWER FE 0W/30

Synthetic motor oil for passenger cars and light commercial vehicles.



## APPLICATION

- **Fuel Economy** - reduce fuel consumption
- passenger cars and light commercial vehicles
- for diesels and petrol engines
- also suitable for hybrid car engines - with frequent turn-off and starts engine
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

## ADVANTAGES

**Qualitium Power FE 0W/30 new generation Fuel-Economy oil for most modern vehicles requiring low viscosity oil**

- perfectly removes solid impurities and reduces the formation of deposits on the pistons and the turbocharger
- appropriately selected formulation so that the low-viscosity oil perfectly lubricates and protects engine against wear
- improved properties in terms of oil flow and "adhesion" to lubricated elements are ideal for vehicles with start-stop systems

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	10,3
Viscosity index	174
Flash point (COC, °C)	228
Pour point (°C)	-42
Total Basic Number (TBN, mg KOH/g)	7,7
HTHS viscosity (mPa·s)	3,1

\* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

## DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo