

QUALITIUM POWER FE 5W/20

<u>Synthetic motor oil for passenger cars and light com-</u> mercial vehicles.



SPECIFICATIONS

SAE: 5W/20

API: SP/SP-RC/SN/CF

ACEA: C5/C6 ILSAC: GF-6

MEETS REQUIREMENTS

Dexos 1 Gen.2, Ford WSS-M2C930-A Ford WSS-M2C925-B Ford WSS-M2C948-B Toyota, Lexus, Nissan Honda, Mazda, Suzuki

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MERCEDES, MITSUBISHI, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

Shell Helix Ultra Professional AF 5W/20 Mobil Super 3000Formula F 5W/20 Castrol Magnatec Stop-start 5W/20 E Platinum Max Expert C5 5W/20 Total Quartz 9000 Future Ecob 5W/20 Elf Evolution Full-Tech Fex 5W/20 Mannol Energy Ultra JP 5W/20

AVAILABLE OIL VOLUMES 1L, 5L, 20L, 60L, 205L, 1000L

APPLICATION

- Fuel Economy reduce fuel consumption
- passenger cars and light commercial vehicles
- for diesels and petrol engines
- also suitable for hybrid car engines with frequent turnoff and starts engine
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium Power FE 5W/20 new generation Fuel-Economy oil for most modern vehicles requiring low viscosity oil

- meets API RC "Resource Conserving" a guarantee of fuel economy when using this oil
- appropriately selected formulation so that the low-viscosity oil perfectly lubricates and protects engine against wear
- improved properties in terms of oil flow and "adhesion" to lubricated elements are ideal for vehicles with start-stop systems

Parameters	Value
Kinematic viscosity at 100°C (mm²/s)	8,6
Viscosity index	165
Flash point (COC, °C)	218
Pour point (°C)	-42
Total Basic Number (TBN, mg KOH/g)	7,9
HTHS viscosity (mPa·s)	2,68

^{*} The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DE-PARTMENT

Qualitium Sp. z o.o. Brzeście Nowe 11B/2, 09-130 Baboszewo