

QUALITIUM POWER FE 5W/20

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 5W/20

API: SP/SP-RC/SN/CF

ACEA: C5/C6

ILSAC: GF-6

MEETS REQUIREMENTS

Dexos 1 Gen.2, Ford WSS-M2C930-A

Ford WSS-M2C925-B

Ford WSS-M2C948-B

Toyota, Lexus, Nissan

Honda, Mazda, Suzuki

May be used in the following vehicles: **AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MERCEDES, MITSUBISHI, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, TOYOTA, VOLKSWAGEN, VOLVO** and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
Max Expert Hybrid 5W20	-	Magnatec 5W/20 E
Elf/TotalEnergies	Orlen Oil	Texaco
Evolution Full-Tech FEX 5W/20 Quartz Ineo ECOB 5W/20	Max Expert Hybrid 5W20	Havoline ProDS F 5W/20

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 60L, 205L, 1000L

APPLICATION

- **Fuel Economy** - reduce fuel consumption
- passenger cars and light commercial vehicles
- for diesels and petrol engines
- also suitable for hybrid car engines - with frequent turn-off and starts engine
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium Power FE 5W/20 new generation Fuel-Economy oil for most modern vehicles requiring low viscosity oil

- meets API RC "Resource Conserving" - a guarantee of fuel economy when using this oil
- appropriately selected formulation so that the low-viscosity oil perfectly lubricates and protects engine against wear
- improved properties in terms of oil flow and "adhesion" to lubricated elements are ideal for vehicles with start-stop systems

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	8.3
Viscosity index	165
Flash point (COC, °C)	218
Pour point (°C)	-45
Total Basic Number (TBN, mg KOH/g)	7.9

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.