

QUALITIUM POWER H 0W/20

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 0W/20

API: SP/SP-RC/SN/CF

ACEA: C5/C6

ILSAC: GF-6

MEETS REQUIREMENTS

Dexos 1 Gen.2

Ford WSS-M2C930-A

Jaguar Land Rover STJLR.03.5004

Toyota, Lexus, Nissan

Honda, Mazda, Suzuki

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MERCEDES, MITSUBISHI, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
Mobil 1 0W/20	-	Edge 0W/20 C5
Elf/TotalEnergies	Orlen Oil	Texaco
-	Max Expert Hybrid 0W/20 Max Expert DEX1 0W/20	Havoline ProDS F 0W/20

AVAILABLE OIL VOLUMES

1L, 4L, 20L, 60L, 205L, 1000L

APPLICATION

- passenger cars and light commercial vehicles
- for diesels and petrol engines
- perfect for hybrid car engines - with frequent turn-off and starts engine
- for engines satisfying Euro 6 emission standards
- engines with DPF/FAP filters as well as three-way catalytic converter (TWC)

ADVANTAGES

Qualitium Power H 0W/20 oil - a perfect balance of excellent quality and low viscosity for modern cars, especially for hybrid cars

- allows to reach the maximum engine power at low and high temperatures
- improved properties in terms of oil flow and "adhesion" to lubricated elements are ideal for vehicles with start-stop systems
- keeps the engine and the exhaust system perfectly clean
- meets API RC "Resource Conserving" - a guarantee of fuel economy when using this oil

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	8.8
Viscosity index	179
Flash point (COC, °C)	215
Pour point (°C)	-48
Total Basic Number (TBN, mg KOH/g)	7.8

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.