


QUALITIUM PROTEC A5/B5 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 5W/30

API: SM/SL/CF

ACEA: A5/B5, A1/B1

MEETS REQUIREMENTS

Ford WSS-M2C913-D

Ford WSS-M2C913-C

Ford WSS-M2C913-B

Ford WSS-M2C913-A

Fiat 9.55535.G1

Renault RN 0700

May be used in the following vehicles:

AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MAZDA, MERCEDES, MITSUBISHI, NISSAN, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, SUZUKI, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
Super 3000 X1 Formula FE 5W/30	Helix Professional AF 5W/30	Edge 5W/30 A5/B5 Magnetec 5W/30 A5 GTX 5W/30 A5/B5
Elf/Totalenergies	Orlen Oil	Texaco
Evolution 900 SXR 5W/30 Quartz 9000 NFC 5W/30	Max Expert F 5W30 Lotos Synthetic A5/B5 5W/30	Havoline Energy 5W/30

APPLICATION

- **meets requirements Ford standards**
- passenger cars and light commercial vehicles
- for diesels and petrol engines
- turbocharged engines and direct injection engines
- severe operating conditions – frequent rides on highways and in city traffic

ADVANTAGES

Qualitium Protec A5/B5 5W/30 reduces wear of engine elements operating at high temperatures even by 15% in comparison to corresponding oils

- stable and high quality of oil at an excellent price
- fast flow to lubrication pairs at very low ambient temperatures – in severe winter conditions
- contributes to fuel economy by reducing friction
- allows developing maximum power of the engine
- prevents deposition of contaminants in the engine

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.4
Viscosity index	160
Flash point (COC, °C)	228
Pour point (°C)	-39
Total Basic Number (TBN, mg KOH/g)	10.3

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 60L, 205L, 1000L