

QUALITIUM POWER C4 5W/30

Synthetic motor oil for passenger cars and light commercial vehicles.



SPECIFICATIONS

SAE: 5W/30

ACEA: C4

ACEA: C1

MEETS REQUIREMENTS

Ford WSS-M2C934-A

Jaguar Land Rover STJLR.03.5005

Renault RN0720

PSA B71-2312

Fiat 9.55535-S4

Mercedes-Benz: 226.51

May be used in the following vehicles: AUDI, BMW, CHEVROLET, CHRYSLER, CITROEN, DACIA, DAEWOO, FIAT, FORD, HONDA, HYUNDAI, KIA, ŁADA, MERCEDES, MITSUBISHI, OPEL, PEUGEOT, RENAULT, ROVER, SAAB, SEAT, SKODA, SUBARU, TOYOTA, VOLKSWAGEN, VOLVO and others when oil of this grade is recommended.

REPLACEMENT OILS

Mobil	Shell	Castrol
Super 3000 Formula R 5W/30	Helix Ultra Professional AR-L 5W/30	GTX 5W/30 C4
Elf/TotaleEnergies	Orlen Oil	Texaco
Evolution R- Tech FE 5W/30; Quartz Ineo C4 5W/30	Max Expert C4 5W/30	Havoline Ultra R 5W/30

AVAILABLE OIL VOLUMES

1L, 4L, 20L, 60L, 205L, 1000L

APPLICATION

- Renault passenger cars and light commercial vehicles or vans requiring RN0720
- passenger cars and light commercial vehicles or vans requiring ACEA C4 for compatibility with GPF or DPF
- for diesels and petrol engines
- for engines satisfying Euro 6 emission standards

ADVANTAGES

Qualitium Power C4 5W/30 new generation oil with standards ACEA C4 and Renault RN0720 for most modern vehicles requiring low viscosity oil

- perfectly removes solid impurities and reduces the formation of deposits on the pistons and the turbocharger.
- appropriately selected formulation so that the low-viscosity oil perfectly lubricates and protects engine against wear
- improved properties in terms of oil flow and "adhesion" to lubricated elements are ideal for vehicles with start-stop systems

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	11.4
Viscosity index	158
Flash point (COC, °C)	222
Pour point (°C)	-39
Total Basic Number (TBN, mg KOH/g)	8.2

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.