



## QUALITIUM GEAR GL-5 75W/80

*Gear oil produced in synthetic technology for passenger cars, light commercial vehicles, trucks, buses and machines.*



### **SPECIFICATIONS**

API: GL-5

SAE: 75W/80

### **MEETS REQUIREMENTS**

API: MT-1

Ford WSD-M2C200-C

Mack GO-J

Mack GO-J Plus

MAN 341 Z2

ZF TE-ML 02B, 08, 17A

DAF, Iveco, Eaton

### **AVAILABLE OIL VOLUMES**

1L, 5L, 20L, 205L, 1000L

### **APPLICATION**

- for transmissions operating in most severe conditions (at high speed and low torque as well as low speed and high torque)
- transmissions and gearboxes in passenger cars and light commercial vehicles
- transmissions and gearboxes in trucks and buses
- transmissions in machines and equipment e.g. for earth-works, where it is recommended to use oil of such API grade

### **ADVANTAGES**

*Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.*

- keeps components of transmission clean
- very good anti-wear properties
- enables easy start-up at low temperatures
- very good thermal stability and resistance to oxidation

Parameters	Value
Kinematic viscosity at 100°C (mm <sup>2</sup> /s)	9,5
Viscosity index	160
Flash point (COC, °C)	222
Pour point (°C)	-40

\*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

### **DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT**

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo