



QUALITIUM GEAR GL-5 75W/80

Gear oil produced in synthetic technology for passenger cars, light commercial vehicles, trucks, buses and machines.

SPECIFICATIONS

API: GL-5

SAE: 75W/80

MEETS REQUIREMENTS

API: MT-1

Ford WSD-M2C200-C

Mack GO-J

Mack GO-J Plus

MAN 341 Z2

ZF TE-ML 02B, 08, 17A

DAF, Iveco, Eaton

REPLACEMENT OILS

Mobil	Fuchs	Castrol
-	-	-
TotalEnergies	Orlen Oil	Shell
Traxium Gear 9 FE 75W/80	Gear SV 75W/80	-

AVAILABLE OIL VOLUMES

1L, 5L, 20L, 205L, 1000L

APPLICATION

- for transmissions operating in most severe conditions (at high speed and low torque as well as low speed and high torque)
- transmissions and gearboxes in passenger cars and light commercial vehicles
- transmissions and gearboxes in trucks and buses
- transmissions in machines and equipment e.g. for earthworks, where it is recommended to use oil of such API grade

ADVANTAGES

Ensures ideal protection from mechanical wear and tear, reduces wear by at least 15% in comparison to corresponding oils.

- keeps components of transmission clean
- very good anti-wear properties
- enables easy start-up at low temperatures
- very good thermal stability and resistance to oxidation

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	9.7
Viscosity index	161
Flash point (COC, °C)	218
Pour point (°C)	-41

*The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo

Guaranteed storage period 3 years from production date. Production date and batch number are on the packaging.