

QUALITIUM RACE 10W/50

Synthetic engine oil for cars and motorcycles operated in extreme conditions



The oil formula used provides excellent protection for engines operated in the most difficult conditions. Oil composed on the basis of PAO and additives resistant to shear and high loads. The technology was created as a result of a long-term research project carried out with scientific units.

SPECIFICATIONS

SAE: 10W/50

API: SM/SL/CF

ACEA: A3/B3/B4

JASO MA-2

JASO T903

AVAILABLE OIL VOLUME

1L, 5L, 60L, 205L

APPLICATION

- for highly stressed car and motorcycle engines with four-stroke engines
- for diesels and petrol engines
- turbocharged engines and direct injection engines
- optimal friction characteristics ensure maximum power transfer, smooth gear changes and adequate protection of the wet clutch
- ideal for quick starting even in very cold conditions or after a long period of engine idleness

ADVANTAGES

Qualitium Race 10W/50 oil significantly exceeds typical parameters of lubricating oil, thus guaranteeing optimal lubrication under above-standard engine loads.

- provides effective protection of engine components under extreme loads
- excellent resistance to oxidation
- allows to obtain maximum engine performance
- prevents deposition of contaminants in the engine
- prevents "slipping" of the clutch in motorcycles with a wet clutch

Parameters	Value
Kinematic viscosity at 100°C (mm ² /s)	18.9
Viscosity index	173
Flash point (COC, °C)	238
Pour point (°C)	-37
Total Basic Number (TBN, mg KOH/g)	10.5

* The above are typical physicochemical values. The actual physicochemical values are to be found in the laboratory report attached to each batch of the product.

DETAILS OF THE COMPANY/TECHNICAL DEPARTMENT

Qualitium Sp. z o.o.

Brzeście Nowe 11B/2, 09-130 Baboszewo